

mahindra
CONSTRUCTION
EQUIPMENT

THE COST EFFECTIVE SOLUTION FOR YOUR LOADING NEEDS

EARTHMASTER SXL 



Give a Missed Call Today:
73037 01222



Also available in 4WD

With
iMAXX
Telematic Remote Care

Backhoe Options	Specification Details	UOM	M&M		
			SXL		
ENGINE	Make		Mahindra		
	Model		NEF 3.5L		
	No. of Cylinders	Nos.	4		
	Displacement	cc	3532		
	Gross Horse Power	HP @ RPM	74HP @ 2200 rpm		
	Peak Gross Torque	Nm@rpm	400 NM @1200-1500 rpm		
	Aspiration		Turbocharged Intercooled		
REFILL CAPACITIES (System Capacity same/ not mentioned if not stated otherwise)	Hydraulic Tank	L	50 L (system - 100 L)		
	Fuel Tank	L	140 L		
	Engine Coolant	L	17 L		
	Engine Oil	L	13 L (system - 13.7 L)		
	Transmission Oil - 2WD	L	10.2 L (system - 19.2 L)		
	Transmission Oil - 4WD	L	12 L (system - 22 L)		
	Rear Axle Oil	L	17.1 L		
	Front Axle Oil	L	2WD - N.A. / 4WD - 9.1 ltrs		
	Brake Reservoir Oil	L	N.A.		
HYDRAULIC SYSTEM	Type		Open Center		
	Pump Type		Gear Pump (52 cm3)		
	Pump Capacity	LPM @ RPM	117 LPM @ 2250 rpm		
	System Pressure	bar	250 Bar		
STEERING SYSTEM	Type		Priority Valve		
	Working Pressure	bar	145 Bar		
TRANSMISSION	Make		Carraro		
	Features		Synchromesh Synchroshuttle		
	Speed		4 Speed (4 Forward/4 Reverse)"		
REAR AXLE	Make		Carraro		
SPEED (GEAR - F/R) (F & R same if not stated otherwise)	1st Forward / Reverse	km/hr	5.43 / 5.66		
	2nd Forward / Reverse	km/hr	8.84 / 9.11		
	3rd Forward / Reverse	km/hr	19.20 / 20.00		
	4th Forward / Reverse	km/hr	38.37 / 39.97		
Dimensions			with 6 in 1 Bucket	With Std Bucket	High Dump Bucket
	Overall Length	mm	5785	5885	6028
	Wheel Base	mm	2176	2176	2176
	Width over Bucket	mm	2456	2404	2416
	Ground Clearance - front axle	mm	350	350	NA
TYRES	Front Tyre		9x16-16PR -2WD 12.5/80 -18	12PR	
	Rear Tyre		16.9X28-12PR (IT Tyre)		
TURNING CIRCLE DIAMETER	Outside Bucket (Inner wheel Braked)	mm	4494		
	Outside Wheels (Inner Wheels Braked)	mm	3091		
	Outside Bucket (Inner wheel not Braked)	mm	5750		
	Outside Wheels (Inner Wheels not Braked)	mm	4400		
ELECTRICALS	Battery Capacity	v	12 V, 100 Ah		
COUNTER WEIGHT	capacity	Kg	1700		

Shipping Weight of Vehicle		2WD/4WD_IT 6 IN 1	2WD/4WD_IT STD Bucket	4WD HD (12 PR) High Dump Bucket
Net Weight of Machine 7710 kg 7579 kg 7788 kg	kg	7710	7579	7788
Front Reaction 2468 kg 2169 kg 2638 kg	kg	2468	2169	2638
Rear Reaction 5174 kg 5410 kg 5150 kg	Kg	5174	5410	5150

Technical specifications, features are subject to change without prior notice. Images used are for representative purpose only. Accessories shown may not be a part of the standard product. Actual colors may vary. E&O.E. ^Standardexclusions apply. For further details on warranty, plesae visit your nearest dealer. ^According to government approved independent agency, under manuracturer standard **PER/VEH/21 certified at 1450 r/min.**

DEALER NAME

***Value measured under specific measuring conditions.**
Mahindra Construction Equipment, Mahindra & Mahindra Ltd. | MCE division | Plot No #A-1/1 , Chakan Industrial Area, Phase-IV, Village Nigoje Chakan, Taluka-Khed, Dist: Pune - 410501, Maharashtra, India.
Toll Free Helpline: 1800 547 0086, **Website:** www.MahindraConstructionEquipment.com **Email:** mce.marketing@mahindra.com